Hippo

Release 0.2.1

Caleb Zulawski

Oct 14, 2019

CONTENTS

1 Hierarchical Information as Pretty-Printed Objects **1**
- 1.1 Introduction . . . 1
- 1.2 Printing user-defined types via reflection . . . 2
- 1.3 Formatting . . . 4
- 1.4 Out-of-the-box type support . . . 9
- 1.5 Advanced usage . . . 11
- 1.6 Can't find what you're looking for? . . . 13

Index **15**

CHAPTER

ONE

HIERARCHICAL INFORMATION AS PRETTY-PRINTED OBJECTS

Hippo is a header-only library for C++17 that provides facilities for pretty-printing user-defined types.

For more information on a specific feature, see the pages below:

1.1 Introduction

1.1.1 Using Hippo

Hippo is a header-only library, so install the headers however you'd like.

To begin using Hippo, include the following:

```
#include "hippo/hippo.h"
```

1.1.2 Printing a value

Printing values is performed by the *hippo::print()* or *hippo::print_to()* functions. Both functions take a value and a *hippo::configuration* and produce a pretty-printed output.

A simple example of printing a vector:

```
#include "hippo/hippo.h"
#include "hippo/std/vector.h"
#include <iostream>

int main() {
  std::vector<int> v {0, 1, 2};
  hippo::print_to(std::cout, v, hippo::configuration());
}
```

This example will print:

```
std::vector [0, 1, 2]
```

1.1.3 Interface

struct configuration
: Global configuration values applied to all printers.

Public Members

std::uint64_t **indent**
The number of spaces to indent for each indentation level (defaults to 0)

std::uint64_t **width**
The number of output columns, not a hard limit but best-effort (defaults to 60)

template<typename **T**>
std::vector<std::string> `hippo::print`(**const** *T* &*t*, **const** hippo::*configuration* &*config*)
Print any printable value `t` with configuration `config`

template<typename **T**>
std::ostream &`hippo::print_to`(std::ostream &*os*, **const** *T* &*t*, **const** hippo::*configuration* &*config*)
Print any printable value `t` with configuration `config` to the specified `std::ostream`

1.2 Printing user-defined types via reflection

A key feature of Hippo is the ease of printing user-defined types.

1.2.1 Classes

Hippo provides utilities for printing user-defined types. Consider the following types:

```
struct Foo {
  int a;
  float b;
};

struct Bar {
  std::vector<Foo> foos;
};
```

To print these types, we reflect them using *HIPPO_CLASS_BEGIN*, *HIPPO_MEMBER*, and *HIPPO_CLASS_END*:

```
#include "hippo/hippo.h"       // reflection macros
#include "hippo/std/vector.h"  // std::vector printer

HIPPO_CLASS_BEGIN(Foo)
  HIPPO_MEMBER(a)
  HIPPO_MEMBER(b)
HIPPO_CLASS_END()

HIPPO_CLASS_BEGIN(Bar)
  HIPPO_MEMBER(foos)
HIPPO_CLASS_END()
```

The printers for `int`, `float`, and `std::vector` are all provided by Hippo. Once we've provided the printer for `Foo`, we are able to use it to print `Bar`. A printed instance of `Bar` might look something like this:

```
Bar {
  foos: std::vector [
    Foo { a: 1, b: 0.5 },
    Foo { a: 2, b: -3.1 }
```

(continues on next page)

(continued from previous page)

```
  ]
}
```

1.2.2 Enums

Like classes, enums can be reflected wish *HIPPO_ENUM_BEGIN*, *HIPPO_ENUM_VALUE*, and *HIPPO_ENUM_END*:

```
enum Foo {
    Bar,
    Baz
};

HIPPO_ENUM_BEGIN(Foo)
  HIPPO_ENUM_VALUE(Bar)
  HIPPO_ENUM_VALUE(Baz)
HIPPO_ENUM_END()
```

1.2.3 Base classes

Hippo can also reflect base classes with *HIPPO_BASE*:

```
struct Foo : Bar {
    /* members */
};

HIPPO_CLASS_BEGIN(Foo)
  HIPPO_BASE(Bar)
  /* members */
HIPPO_CLASS_END()
```

1.2.4 Custom member access expressions

In some cases, it's useful to use another expression to access a member. This is accomplished by using the *HIPPO_MEMBER_EXPR* macro, which allows a custom expression to be provided, operating on the input `object`:

```
class Foo {
    int bar;
public:
    Foo(int bar) : bar(bar) {}
    int get_bar() const { return bar; }
};

HIPPO_CLASS_BEGIN(Foo)
  HIPPO_MEMBER_EXPR(bar, object.get_bar())
HIPPO_CLASS_END()
```

1.2.5 Interface

Class reflection

HIPPO_CLASS_BEGIN(Type)
Begin the definition of a printer specialization for a class `Type`

HIPPO_CLASS_END()
End the definition of a printer specialization for a class.

HIPPO_BASE(Type)
Register `Type` as a base class in a class printer specialization.

HIPPO_MEMBER(Name)
Register `Name` as a member in a class printer specialization.

HIPPO_MEMBER_EXPR(Name, Expression)
Register `Name` as a member, printed as `Expression`, in a class printer specialization.

Enum reflection

HIPPO_ENUM_BEGIN(Type)
Begin the definition of a printer specialization for an enum `Type`

HIPPO_ENUM_END()
End the definition of a printer specialization for an enum.

HIPPO_ENUM_VALUE(Value)
Register an enum value named `Value`

1.3 Formatting

Some printable types support formatting. Formatting is applied with the *`hippo::formatter`* adapter, which itself is a printable type that applies a format to its contents.

1.3.1 Formatting numbers

The following example shows how numbers can be formatted for a user-defined type:

```
struct Foo {
  int bar;
  float baz;
};

static hippo::integer_format hex() {
  hippo::integer_format fmt;
  fmt.base = hippo::integer_format::base_type::hex;
  return fmt;
}

static hippo::float_format scientific() {
  hippo::float_format fmt;
  fmt.format = hippo::float_format::notation_type::scientific;
  return fmt;
};
```

(continues on next page)

(continued from previous page)

```
HIPPO_CLASS_BEGIN(Foo)
  HIPPO_CLASS_MEMBER_EXPR(Foo, hippo::formatter(object.bar, hex()))
  HIPPO_CLASS_MEMBER_EXPR(Foo, hippo::formatter(object.baz, scientific()))
HIPPO_CLASS_END()
```

1.3.2 Using formatting to print polymorphic types

Polymorphic types can be printed by use of *hippo::derived_type_printer*:

```
#include "hippo/hippo.h"
#include "hippo/std/memory.h"
#include <iostream>

struct Foo {
  virtual ~Foo() = default;
};

struct Bar : Foo {};
struct Baz : Foo {};

HIPPO_CLASS_BEGIN(Foo)
HIPPO_CLASS_END()

HIPPO_CLASS_BEGIN(Bar)
  HIPPO_BASE(Foo)
HIPPO_CLASS_END()

HIPPO_CLASS_BEGIN(Baz)
  HIPPO_BASE(Foo)
HIPPO_CLASS_END()

int main() {
  std::shared_ptr<Foo> foo = std::make_shared<Foo>();
  std::shared_ptr<Foo> bar = std::make_shared<Bar>();
  std::shared_ptr<Foo> baz = std::make_shared<Baz>();
  hippo::dynamic_type_format<Foo> dyn_fmt;
  dyn_fmt.printers.push_back(std::make_shared<hippo::derived_type_printer<Foo, Bar>>
↪());
  dyn_fmt.printers.push_back(std::make_shared<hippo::derived_type_printer<Foo, Baz>>
↪());
  hippo::pointer_format<Foo> fmt = std::move(dyn_fmt);
  hippo::print_to(std::cout, hippo::formatter(foo, fmt), hippo::configuration());
  hippo::print_to(std::cout, hippo::formatter(bar, fmt), hippo::configuration());
  hippo::print_to(std::cout, hippo::formatter(baz, fmt), hippo::configuration());
}
```

Once `Bar` and `Baz` are registered with the pointer format, the printer is able to use RTTI to determine which printer to use. The following is printed:

```
std::shared_ptr containing [ Foo { } ]
std::shared_ptr containing [ Bar { Base Foo { } } ]
std::shared_ptr containing [ Baz { Base Foo { } } ]
```

1.3.3 Interface

template<typename **T**>
struct formatter
A printable type that applies formats to other printable types.

Public Types

template<>
using value_type = std::remove_const_t<T>
The type to format.

template<>
using printer_type = hippo::*printer*<*value_type*>
The printer for `T`

template<>
using format_type = **typename** *printer_type*::format_type
The format configuration for `T`

Public Functions

formatter(**const** value_type &*value*, **const** format_type &*format*)
Construct a `formatter` that prints `value` with the format described by `format`. The constructed `formatter` does not own `value` or `format`, so both must remain in scope for the lifetime of the `formatter`.

template<typename **T**>
struct formatter<*T* *>
Specialization of `formatter` for pointer types.

Public Types

template<>
using value_type = std::remove_const_t<std::decay_t<T>>
The type to format.

template<>
using printer_type = hippo::*printer*<*value_type* *>
The printer for `T`

template<>
using format_type = **typename** *printer_type*::format_type
The format configuration for `T`

Public Functions

formatter(**const** value_type *value, **const** format_type &*format*)
Construct a `formatter` that prints `value` with the format described by `format`. The constructed `formatter` does not own `value` or `format`, so both must remain in scope for the lifetime of the `formatter`.

struct no_format
Format for non-formattable types.

Number format configurations

struct integer_format
Format for integer values.

Public Types

enum base_type
Integer base description.

Values:

oct
Octal.

dec
Decimal.

hex
Hexadecimal.

Public Members

base_type **base**
Numeric base.

struct float_format
Format for floating-point values.

Public Types

enum notation_type
Notation format description.

Values:

standard
Format with `std::defaultfloat`

fixed
Format with `std::fixed`

scientific
Format with `std::scientific`

Public Members

notation_type **notation**
Notation format, defaults to `standard`

std::optional<std::size_t> **precision**
Precision for `std::setprecision`

Pointer configurations

using `hippo::`**pointer_format** = std::variant<standard_pointer_format<T>, *address_format*, dynamic_type_format<T>>
Format for printing a pointer.

template<typename **T**>
struct standard_pointer_format
Format option for non-polymorphic pointers. A non-null pointer is dereferenced and printed.

Public Types

template<>
using format_type = **typename** hippo::*printer*::format_type
Format type of `T`

Public Members

format_type **format**
The format used for printing.

struct address_format
Format option for printing pointers as addresses (rather than printing the dereferenced pointer)

template<typename **T**>
struct dynamic_type_format
Format option for printing polymorphic types. A non-null pointer is checked against the registered types, dereferenced, and printed.

Public Types

template<>
using base_format_type = **typename** hippo::*printer*<T>::format_type
Format type of the base class.

Public Members

std::vector<std::shared_ptr<base_type_printer<T>>> **printers**
Printers for derived types, in preference order.

Printers are called one by one and returns the first successful output.

base_format_type **base_format**
If none of the derived printers are successful, the base class is printed with this format.

template<typename **Base**>
struct base_type_printer
Abstract base for printers of polymorphic pointers.

Subclassed by *hippo::derived_type_printer< Base, Derived >*

Public Functions

virtual std::optional<hippo::*object*> **print**(**const** Base **b*, std::uint64_t *current_indent*, **const** hippo::*configuration* &*config*) = 0
Prints `b` if possible, otherwise the return value is empty.

template<typename **Base**, typename **Derived**>
struct derived_type_printer : **public** hippo::base_type_printer<*Base*>
Printer for a polymorphic type from a base class pointer.

Public Types

template<>
using printer_type = hippo::*printer*<Derived>
Printer specialization for `Derived`

template<>
using format_type = **typename** *printer_type*::format_type
Format type of `Derived`

Public Functions

derived_type_printer()
Construct a printer using the default format.

derived_type_printer(**const** format_type &*format*)
Construct a printer using the specified format `format`

std::optional<hippo::*object*> **print**(**const** Base **b*, std::uint64_t *current_indent*, **const** hippo::*configuration* &*config*)
Prints `b` if it is a `Derived`, otherwise returns nothing.

1.4 Out-of-the-box type support

As discussed in *Printing user-defined types via reflection*, `struct`, `class`, `enum`, and `enum class` are all supported via macros.

In addition to user defined types, most types provided by the language are automatically supported. All builtin types are supported, as well as many from the standard library.

1.4.1 Supported standard library types

Strings

In addition to `const char *`, Hippo supports `std::string` via `"hippo/std/string.h"`.

Containers

Support for all containers is available:

- `std::array` via `"hippo/std/array.h"`

- `std::vector` via `"hippo/std/vector.h"`
- `std::list` via `"hippo/std/list.h"`
- `std::forward_list` via `"hippo/std/forward_list.h"`
- `std::deque` via `"hippo/std/deque.h"`
- `std::set` and `std::multiset` via `"hippo/std/set.h"`
- `std::unordered_set` and `std::unordered_multiset` via `"hippo/std/unordered_set.h"`
- `std::map` and `std::multimap` via `"hippo/std/map.h"`
- `std::unordered_map` and `std::unordered_multimap` via `"hippo/std/unordered_map.h"`

All containers can be formatted with the format configuration of the inner type(s). Map types can be formatted with:

using `hippo::`**map_format** = std::pair<**typename** hippo::*printer*<Key>::format_type, **typename** hippo::*printer*<Value>::form
Format for map types.

Tuples

Both `std::pair` and `std::tuple` are supported, by `"hippo/std/utility.h"` and `"hippo/std/tuple.h"`, respectively.

They can be formatted with:

using `hippo::`**pair_format** = std::pair<**typename** hippo::*printer*<First>::format_type, **typename** hippo::*printer*<Second>::
Format for `std::pair`

using `hippo::`**tuple_format** = std::tuple<**typename** hippo::*printer*<T>::format_type...>
Format for `std::tuple`

Smart pointers

In addition to plain pointers, `std::unique_ptr`, `std::shared_ptr`, and `std::weak_ptr` are supported via `"hippo/std/memory.h"`. These types are all formattable by *`hippo::pointer_format`*.

Sum types

`std::optional` is supported via `"hippo/std/optional.h"` and is formattable with the inner type's format configuration. `std::variant` is supported via `"hippo/std/variant.h"` and is formattable with:

using `hippo::`**variant_format** = std::tuple<**typename** hippo::*printer*<T>::format_type...>

Chrono

`std::chrono::duration` is supported via `"hippo/std/chrono.h"` and is formattable with the inner type's format configuration.

Complex

`std::complex` is supported via `"hippo/std/complex.h"` and is formattable with the inner type's format configuration.

Atomic

`std::atomic` is supported via `"hippo/std/atomic.h"` and is formattable with the inner type's format configuration.

Bitset

`std::bitset` is supported via `"hippo/std/bitset.h"` and is not formattable.

1.5 Advanced usage

Sometimes it is necessary to access the internal workings to create a more complicated printer.

1.5.1 Representing of lines of text

Before we get into printing types, we must understand how outputs are represented. In Hippo, a line of text is represented by *`hippo::line`*, which tracks the indentation level of the line separately from the contents.

`struct line`
Describes a printed line of text.

Public Functions

`line`(std::uint64_t *indent*)
Construct an empty line with the given indentation level.

`line`(std::uint64_t *indent*, std::string *string*)
Construct a line with the given indentation level and string.

Public Members

std::uint64_t **`indent`**
The indentation level of the line.

std::string **`string`**
The contents of the line.

When an object is printed, the generated lines of text are then collected into a *`hippo::object`*. Any lines that are shorter than *`hippo::configuration::width`* are condensed into a single line if possible. Multiple *`hippo::object`* may be condensed as well, but only if all of the objects are a single line.

`using` `hippo::`**`object`** = std::variant<hippo::*line*, std::list<hippo::*line*>>
Describes the printed output of any object, either as a single or multiple lines.

`inline` hippo::*object* `hippo::`**`condense`**(**`const`** std::list<hippo::*line*> &*lines*, **`const`** hippo::*configuration* &*config*)
Condense a collection of `lines` into a single `object`. Multiple lines will be condensed into one if the indented result is less than the configured output width.

inline hippo::*object* `hippo::` **condense** (**const** std::list<hippo::*object*> *&objects*, **const** hippo::*configuration* *&config*)

Condense a collection of `objects` into a single `object`. If any of the input `objects` are multiline, the output is not condensed, otherwise the lines will condensed if the indented result is less than the configured output width.

1.5.2 Defining a printer

Printers are added for a type by specializing the *`hippo::printer`* struct. This class is declared as follows:

template<typename **T**, typename **U** = *T*>
struct printer

The core pretty-printer type. `T` is the type to be printed. `U` is provided for optionally making SFINAE possible.

Specializations must fulfill the following interface:

```
template<> hippo::printer<Foo> {
  using format_type = /* any default-constructible and copy-constructible type */
  static ::hippo::object print(const Foo &f,
                               std::uint64_t current_indent,
                               const ::hippo::configuration &config,
                               const format_type &format = format_type());

}
```

1.5.3 Convenient utilities

The following operations are so common when creating printers that Hippo provides them.

Manipulating lines

struct prepend_visitor

Visitor over `objects` that prepends a string to the first line.

Public Functions

void **operator()** (hippo::*line* *&line*)

Prepend to a single line.

void **operator()** (std::list<hippo::*line*> *&lines*)

Prepend to the beginning of many lines.

Public Members

std::string **prefix**

The string to prepend.

struct append_visitor

Visitor over `objects` that appends a string to the last line.

Public Functions

void **operator()**(hippo::*line* &*line*)
Append to a single line.

void **operator()**(std::list<hippo::*line*> &*lines*)
Append to the end of many lines.

Public Members

std::string **suffix**
The string to append.

Formatting values

template<typename **T**>
std::enable_if_t<std::is_floating_point_v<*T*>, std::string> `hippo::`**apply_format**(*T* *value*, **const** *float_format* &*fmt*)
Apply format `fmt` to floating-point `value`

template<typename **T**>
std::enable_if_t<std::is_integral_v<*T*>, std::string> `hippo::`**apply_format**(*T* *value*, **const** *integer_format* &*fmt*)
Apply format `fmt` to integer `value`

template<typename **T**>
hippo::*object* `hippo::`**apply_format**(**const** *T* **value*, std::uint64_t *current_indent*, **const** hippo::*configuration* &*config*, **const** *pointer_format*<*T*> &*fmt*)
Apply format `fmt` to pointer `value` using the `current_indent` indentation level and configuration `config`.

1.6 Can't find what you're looking for?

- genindex
- search

INDEX

H

hippo::address_format (*C++ class*), 8
hippo::append_visitor (*C++ class*), 12
hippo::append_visitor::operator() (*C++ function*), 13
hippo::append_visitor::suffix (*C++ member*), 13
hippo::apply_format (*C++ function*), 13
hippo::base_type_printer (*C++ class*), 8
hippo::base_type_printer::print (*C++ function*), 9
hippo::condense (*C++ function*), 11
hippo::configuration (*C++ class*), 1
hippo::configuration::indent (*C++ member*), 2
hippo::configuration::width (*C++ member*), 2
hippo::derived_type_printer (*C++ class*), 9
hippo::derived_type_printer::derived_type_printer (*C++ function*), 9
hippo::derived_type_printer::print (*C++ function*), 9
hippo::derived_type_printer<Base, Derived>::format_type (*C++ type*), 9
hippo::derived_type_printer<Base, Derived>::printer_type (*C++ type*), 9
hippo::dynamic_type_format (*C++ class*), 8
hippo::dynamic_type_format::base_format (*C++ member*), 8
hippo::dynamic_type_format::printers (*C++ member*), 8
hippo::dynamic_type_format<T>::base_format_type (*C++ type*), 8
hippo::float_format (*C++ class*), 7
hippo::float_format::fixed (*C++ enumerator*), 7
hippo::float_format::notation (*C++ member*), 7
hippo::float_format::notation_type (*C++ enum*), 7
hippo::float_format::precision (*C++ member*), 7
hippo::float_format::scientific (*C++ enumerator*), 7
hippo::float_format::standard (*C++ enumerator*), 7
hippo::formatter (*C++ class*), 6
hippo::formatter::formatter (*C++ function*), 6
hippo::formatter<T *> (*C++ class*), 6
hippo::formatter<T *>::format_type (*C++ type*), 6
hippo::formatter<T *>::printer_type (*C++ type*), 6
hippo::formatter<T *>::value_type (*C++ type*), 6
hippo::formatter<T>::format_type (*C++ type*), 6
hippo::formatter<T>::printer_type (*C++ type*), 6
hippo::formatter<T>::value_type (*C++ type*), 6
hippo::integer_format (*C++ class*), 7
hippo::integer_format::base (*C++ member*), 7
hippo::integer_format::base_type (*C++ enum*), 7
hippo::integer_format::dec (*C++ enumerator*), 7
hippo::integer_format::hex (*C++ enumerator*), 7
hippo::integer_format::oct (*C++ enumerator*), 7
hippo::line (*C++ class*), 11
hippo::line::indent (*C++ member*), 11
hippo::line::line (*C++ function*), 11
hippo::line::string (*C++ member*), 11
hippo::map_format (*C++ type*), 10
hippo::no_format (*C++ class*), 6
hippo::object (*C++ type*), 11
hippo::pair_format (*C++ type*), 10
hippo::pointer_format (*C++ type*), 8
hippo::prepend_visitor (*C++ class*), 12

hippo::prepend_visitor::operator() (*C++ function*), 12
hippo::prepend_visitor::prefix (*C++ member*), 12
hippo::print (*C++ function*), 2
hippo::print_to (*C++ function*), 2
hippo::printer (*C++ class*), 12
hippo::standard_pointer_format (*C++ class*), 8
hippo::standard_pointer_format::format (*C++ member*), 8
hippo::standard_pointer_format<T>::format_type (*C++ type*), 8
hippo::tuple_format (*C++ type*), 10
hippo::variant_format (*C++ type*), 10
HIPPO_BASE (*C macro*), 4
HIPPO_CLASS_BEGIN (*C macro*), 4
HIPPO_CLASS_END (*C macro*), 4
HIPPO_ENUM_BEGIN (*C macro*), 4
HIPPO_ENUM_END (*C macro*), 4
HIPPO_ENUM_VALUE (*C macro*), 4
HIPPO_MEMBER (*C macro*), 4
HIPPO_MEMBER_EXPR (*C macro*), 4